



Parker Hannifin Corporation
Industrial Hose Division
17295 Foltz Industrial Pkwy
Strongsville, OH 44149
Telephone: (440) 268-2120
Fax: (440) 268-2230
www.safehose.com

PRODUCT UPDATE

Series 7216 Translite® Tank Truck Hose - Nitrile Cover & Dual Branding (SW309) **Series SW309 Petrovac Hose - Obsolete**



In order to streamline the product offering, Parker is now combining Series 7216 and Series SW309 petroleum products into an updated 7216 Series. This "Dual Branded" product combines the best design aspects of both products into the new and improved Series 7216. As a result, the stand-alone SW309 Series hose will be obsolete when current inventory is depleted, and will no longer be manufactured.

The two changes that will be incorporated into new production of Series 7216 are a nitrile cover, and a cross-reference to Series SW309 in the standard brand. Series 7216 part numbers and pricing will not change. In addition, any current quotations for SW309 part numbers will be converted to 7216 part numbers without change to pricing.

Please see comparison chart on page 2.

If there are any questions please contact
Parker Customer Service toll-free at:

866.810.HOSE (4673)
Strongsville, OH
Eastern USA

800.242.HOSE (4673)
South Gate, CA
Western USA

(Continued on page 2)



Series 7216 Translite® Tank Truck Hose - Nitrile Cover & Dual Branding (SW309)

	<u>New 7216 / SW309</u>	<u>Previous 7216</u>	<u>Previous SW309</u>
Tube:	Black nitrile	Black nitrile	Black nitrile
Reinforcement:	Multiple textile plies w/ wire helix(es)	Multiple textile plies w/ wire helix	Multiple textile plies w/ dual wire helix
Cover:	Black nitrile; wrapped finish	Black Neoprene; wrapped finish	Black nitrile; wrapped finish
Temp Range:	-40°F to +180°F	-20°F to +180°F	-40°F to +180°F
Size Range:	1" to 8"	1" to 8"	1" to 6"
Design Factor:	4:1	4:1	4:1
Brand Method:	Black text on orange stripe	Black text on orange stripe	Black text on red stripe
Brand Example: (7216/SW309)	PARKER SERIES 7216 / SW309 TRANSLITE® TANK TRUCK HOSE 150 PSI MADE IN USA 001		
Applications:	Petroleum suction and discharge; tank trucks		
Compare To:	Eaton Boston Puma; Gates Longhorn; Veyance Plicord Flexwing		

Part Number	ID (in)	ID (mm)	Reinf Layers	OD (in)	OD (mm)	Approx Wt (lbs)/ 100 ft	Min Bend Rad (in)	Max Rec WP (psi)	Std Pack Qty (ft)
7216-1002	1	25.4	2	1.364	34.6	42	2	150	100
7216-1252	1-1/4	31.8	2	1.670	42.4	59	3	150	100
7216-1502	1-1/2	38.1	2	1.968	49.8	84	4	150	100
7216-2002	2	50.8	2	2.512	63.8	110	6	150	100
7216-2502	2-1/2	63.5	2	3.028	76.9	144	9	150	100
7216-3002	3	76.2	2	3.543	90.2	183	12	150	100
7216-4002	4	102.0	2	6.646	168.8	297	16	150	100
7216-4504	4-1/2	114.3	4	5.220	118.1	351	24	150	100
7216-5004	5	127.0	4	5.787	146.0	446	39	150	100
7216-6004	6	152.4	4	6.811	172.0	579	48	150	100
7216-8004	8	203.2	4	8.976	225.8	942	72	75	50

Packaging: Coils
Couplings: Permanent crimp: refer to CrimpSource @ www.safehose.com
 Other coupling options: refer to NAHAD Industrial Hose Assembly Guidelines

WARNING: Non-crimp couplings applied with bands or clamps may reduce the working pressure of the hose assembly to less than that of the maximum rated working pressure of the hose. Refer to the NAHAD Industrial Hose Assembly Specification Guidelines for working pressure information.