



Sales Advisory

Parker Hannifin Corporation
Industrial Hose Division
17295 Foltz Industrial Pkwy
Strongsville, OH 44149
Telephone: (440) 268-2120
Fax: (440) 268-2230
www.safehose.com

PRODUCT INFORMATION

Series SW303 Petroleum Suction & Discharge Hose – Obsolete

Refer to Series 7216 Translite® Tank Truck Hose



To streamline the petroleum hose product offering, Series SW303 suction and discharge hose will be obsolete when current inventory is depleted. The discontinuation applies to both standard and non-standard part numbers within the product line, and all quotations will be expired with the discontinuation. Parker continues to offer Series 7216 Translite tank truck hose as a suggested replacement.

If there are any questions please contact
Parker Customer Service toll-free at:

866.810.HOSE (4673)
Strongsville, OH
Eastern USA

800.242.HOSE (4673)
South Gate, CA
Western USA

(Continued on page 2)

PA 2010.04.002 Series SW303 OBS - 7216 REPL

ENGINEERING YOUR SUCCESS.



Series SW303 Petroleum Suction & Discharge Hose – Obsolete

Refer to Series 7216 Translite® Tank Truck Hose

	<u>Series 7216</u>	<u>Series SW303</u>
Tube:	Black nitrile	Black nitrile
Reinforcement:	Multiple textile plies w/ wire helix(es)	Multiple textile plies w/ dual wire helix
Cover:	Black nitrile; wrapped finish	Black nitrile; wrapped finish
Temp Range:	-40°F to +180°F	-40°F to +180°F
Size Range:	1" to 10"	1-1/4" to 4"
Design Factor:	4:1	4:1
Brand Method:	Black text on orange stripe	Black text on red stripe
Brand Example:	PARKER SERIES 7216 / SW309 TRANSLITE® TANK TRUCK HOSE 150 PSI MADE IN USA	
Applications:	Petroleum suction and discharge; tank trucks	
Compare To:	Eaton Boston Puma; Gates Longhorn; Veyance Plicord Flexwing	

Part Number	ID (in)	ID (mm)	Reinf Layers	OD (in)	OD (mm)	Approx Wt (lbs)/ 100 ft	Min Bend Rad (in)	Max Rec WP (psi)	Std Pack Qty (ft)
7216-1252	1-1/4	31.8	2	1.670	42.4	59	3	150	100
7216-1502	1-1/2	38.1	2	1.968	49.8	84	4	150	100
7216-2002	2	50.8	2	2.512	63.8	110	6	150	100
7216-2502	2-1/2	63.5	2	3.028	76.9	144	9	150	100
7216-3002	3	76.2	2	3.543	90.2	183	12	150	100
7216-4002	4	102.0	2	6.646	168.8	297	16	150	100
SW303-1250	1-1/4	31.8	2	1.688	42.9	51	4	200	100
SW303-1500	1-1/2	38.1	2	2.000	50.8	64	5	200	100
SW303-2000	2	50.8	2	2.500	63.5	95	6	200	100
SW303-2500	2-1/2	63.5	2	3.000	76.2	132	8	150	100
SW303-3000	3	76.2	2	3.500	88.9	168	12	150	100
SW303-4000	4	102.0	2	4.625	117.5	263	18	150	100

Packaging: Coils
Couplings: Permanent crimp: refer to CrimpSource® @ www.safehose.com
 Other coupling options: refer to NAHAD Industrial Hose Assembly Guidelines

WARNING: Non-crimp couplings applied with bands or clamps may reduce the working pressure of the hose assembly to less than that of the maximum rated working pressure of the hose. Refer to the NAHAD Industrial Hose Assembly Specification Guidelines for working pressure information.