



Sales Advisory

Parker Hannifin Corporation
Industrial Hose Division
17295 Foltz Industrial Pkwy
Strongsville, OH 44149
Telephone: (440) 268-2120
Fax: (440) 268-2230
www.safehose.com

PRODUCT INFORMATION

Series SW308 Spartan™ Tank Truck Hose – Obsolete

Refer to Series 7216E Translite® Equalizer Tank Truck Hose



To streamline the petroleum hose product offering, Series SW308 Spartan tank truck hose will be obsolete when current inventory is depleted. The discontinuation applies to both standard and non-standard part numbers within the product line, and all quotations will be expired with the discontinuation. Parker continues to offer Series 7216E Translite Equalizer tank truck hose as a suggested replacement.

If there are any questions please contact
Parker Customer Service toll-free at:

866.810.HOSE (4673)
Strongsville, OH
Eastern USA

800.242.HOSE (4673)
South Gate, CA
Western USA

(Continued on page 2)

PA 2010.04.003 Series SW308 OBS - 7216E REPL

ENGINEERING YOUR SUCCESS.



Series SW308 Spartan™ Tank Truck Hose – Obsolete

Refer to Series 7216E Translite® Equalizer Tank Truck Hose

	<u>Series 7216E</u>	<u>Series SW308</u>
Tube:	Black nitrile	Black nitrile
Reinforcement:	Multiple textile plies w/ dual wire helix	Multiple textile plies w/ wire helix
Cover:	Black Neoprene; wrapped finish	Black nitrile; wrapped finish
Temp Range:	-30°F to +180°F	-40°F to +180°F
Size Range:	1" to 8"	2" to 4"
Design Factor:	3:1	4:1
Brand Method:	Black text on orange stripe	Black text on red stripe
Brand Example:	PARKER SERIES 7216E TRANSLITE® TANK TRUCK HOSE 150 PSI MAX WP	
Applications:	Petroleum suction and discharge; tank trucks	
Compare To:	Veyance Plicord Super Black Flexwing	

Part Number	ID (in)	ID (mm)	Reinf Layers	OD (in)	OD (mm)	Approx Wt (lbs)/100 ft	Min Bend Rad (in)	Max Rec WP (psi)	Std Pack Qty (ft)
7216E-2002	2	50.8	2	2.500	63.5	110	6	150	100
7216E-3002	3-3/100	77.0	2	3.620	91.9	208	12	150	100
7216E-4002	4	102.0	2	4.650	118.1	280	16	150	100
SW308-2000	2	50.8	2	2.450	62.2	97	10	150	100
SW308-3000	3	76.2	2	3.500	88.9	163	14	150	100
SW308-4000	4	102.0	2	4.500	114.3	230	22	150	100

Packaging: Coils

Couplings: Permanent crimp: refer to CrimpSource® @ www.safehose.com
Other coupling options: refer to NAHAD Industrial Hose Assembly Guidelines

WARNING: Non-crimp couplings applied with bands or clamps may reduce the working pressure of the hose assembly to less than that of the maximum rated working pressure of the hose. Refer to the NAHAD Industrial Hose Assembly Specification Guidelines for working pressure information.