



Parker Hannifin Corporation
Industrial Hose Division
17295 Foltz Industrial Pkwy
Strongsville, OH 44149
Telephone: (440) 268-2120
Fax: (440) 268-2230
www.safehose.com

PRODUCT INFORMATION

Series 7222 Gold Label[®] Corrugated Tank Truck Hose – Obsolete
*Refer to Series SWC609 Titanflex[®] Corrugated Petroleum Suction
and Discharge Hose*



To streamline the petroleum hose product offering, Series 7222 Gold Label corrugated tank truck hose will be obsolete when current inventory is depleted. The discontinuation applies to both standard and non-standard part numbers within the product line, and all quotations will be expired with the discontinuation. Parker continues to offer Series SWC609 Titanflex corrugated petroleum suction and discharge hose as a suggested replacement.

If there are any questions please contact
Parker Customer Service toll-free at:

866.810.HOSE (4673)
Strongsville, OH
Eastern USA

800.242.HOSE (4673)
South Gate, CA
Western USA

(Continued on page 2)

PA 2010.04.004 Series 7222 OBS - SWC609 REPL



Series 7222 Gold Label[®] Corrugated Tank Truck Hose – Obsolete *Refer to Series SWC609 Titanflex[®] Corrugated Petroleum Suction and Discharge Hose*

	<u>Series SWC609</u>	<u>Series 7222</u>
Tube:	Black nitrile	Black nitrile
Reinforcement:	Multiple textile plies w/ dual wire helix	Multiple textile plies w/ dual wire helix
Cover:	Black nitrile; corrugated wrapped finish	Black Neoprene; corrugated wrapped finish
Temp Range:	-40°F to +180°F	-20°F to +180°F
Size Range:	1-1/2" to 6"	1-1/4" to 4"
Design Factor:	4:1	4:1
Brand Method:	Red text on black stripe	Black text on gold stripe
Brand Example:	PARKER SWC609 TITANFLEX [®] PETROLEUM SUCTION HOSE 2" 250 PSI WP (Caution) MADE IN USA	
Applications:	Petroleum suction and discharge; tank trucks	
Compare To:	Eaton Boston Bobcat; Gates Longhorn; Thermoid Transporter; Veyance Flextra	

Part Number	ID (in)	ID (mm)	Reinf Layers	OD (in)	OD (mm)	Approx Wt (lbs)/ 100 ft	Min Bend Rad (in)	Max Rec WP (psi)	Std Pack Qty (ft)
SWC609-1500	1-1/2	38.1	2	2.063	52.4	72	2	250	100
SWC609-2000	2	50.8	2	2.563	65.1	92	2	250	100
SWC609-2500	2-1/2	63.5	2	3.188	81.0	135	3	200	100
SWC609-3000	3	76.2	2	3.688	93.7	170	3	200	100
SWC609-4000	4	102.0	2	4.625	117.5	241	4	150	100
7222-150150	1-1/2	38.1	2	1.969	50.0	79	3	200	100
7222-200150	2	50.8	2	2.440	62.0	95	4	200	100
7222-250150	2-1/2	63.5	2	3.028	76.9	130	5	200	100
7222-300150	3	76.2	2	3.488	88.6	170	5	200	100
7222-400150	4	102.0	2	4.527	115.0	225	6	150	100

Packaging: Coils
Couplings: Permanent crimp: refer to CrimpSource[®] @ www.safehose.com
 Other coupling options: refer to NAHAD Industrial Hose Assembly Guidelines

WARNING: Non-crimp couplings applied with bands or clamps may reduce the working pressure of the hose assembly to less than that of the maximum rated working pressure of the hose. Refer to the NAHAD Industrial Hose Assembly Specification Guidelines for working pressure information.