



Parker Hannifin Corporation
Industrial Hose Division
17295 Foltz Industrial Pkwy
Strongsville, OH 44149
Telephone: (440) 268-2120
Fax: (440) 268-2230
www.safehose.com

PRODUCT INFORMATION

Series 7220 Silver Label™ and Series 7223 Gold Label®

Corrugated Tank Truck Hose – Obsolete

*Refer to Series SWC609R Titanflex® Corrugated Petroleum
Suction and Discharge Hose*



To streamline the petroleum hose product offering, Series 7220 Silver Label and Series 7223 Gold Label corrugated tank truck hose will be obsolete when current inventory is depleted. The discontinuation applies to both standard and non-standard part numbers within the respective product lines, and all quotations will be expired with the discontinuation. Parker continues to offer Series SWC609R Titanflex petroleum suction and discharge hose as a suggested replacement.

If there are any questions please contact
Parker Customer Service toll-free at:

866.810.HOSE (4673)
Strongsville, OH
Eastern USA

800.242.HOSE (4673)
South Gate, CA
Western USA

(Continued on page 2)



Series 7220 Silver Label™ and Series 7223 Gold Label®
Corrugated Tank Truck Hose – Obsolete
Refer to Series SWC609R Titanflex® Corrugated Petroleum
Suction and Discharge Hose

	<u>Series SWC609R</u>	<u>Series 7220</u>	<u>Series 7223</u>
Tube:	Black nitrile	Black nitrile	Black nitrile
Reinforcement:	Mult. textile plies w/ dual helix	Mult. textile plies w/ dual helix	Mult. textile plies w/ dual helix
Cover:	Red nitrile; corr. wrapped finish	Red Neoprene; corr. wrapped	Red Neoprene; corr. wrapped
Temp Range:	-40°F to +180°F	-20°F to +180°F	-20°F to +180°F
Size Range:	1-1/2" to 6"	2" to 4"	1-1/2" to 4"
Design Factor:	4:1	4:1	4:1
Brand Method:	White text on red stripe	Silver text on red stripe	Red text on gold stripe
Brand Example:	PARKER SWC609R TITANFLEX® PETROLEUM SUCTION HOSE 2" 250 PSI WP (Caution) MADE IN USA		
Applications:	Petroleum suction and discharge; tank trucks		
Compare To:	Eaton Boston Bobcat; Gates Longhorn; Thermoid Transporter; Veyance Flextra		

Part Number	ID (in)	ID (mm)	Reinf Layers	OD (in)	OD (mm)	Approx Wt (lbs)/ 100 ft	Min Bend Rad (in)	Max Rec WP (psi)	Std Pack Qty (ft)
SWC609R-1500	1-1/2	38.1	2	2.063	52.4	72	2	250	100
SWC609R-2000	2	50.8	2	2.563	65.1	92	2	250	100
SWC609R-2500	2-1/2	63.5	2	3.188	81.0	135	3	200	100
SWC609R-3000	3	76.2	2	3.688	93.7	174	3	200	100
SWC609R-4000	4	102.0	2	4.625	117.5	246	4	150	100
7220-2000	2	50.8	2	2.440	62.0	96	4	150	100
7220-2500	2-1/2	63.5	2	2.953	75.0	136	5	150	100
7220-3000	3	76.2	2	3.465	88.0	150	6	150	100
7220-4000	4	102.0	2	4.527	115.0	231	9	150	100
7223-150150	1-1/2	38.1	2	1.969	50.0	79	3	200	100
7223-200150	2	50.8	2	2.440	62.0	95	4	200	100
7223-250150	2-1/2	63.5	2	3.028	76.9	130	5	200	100
7223-300150	3	76.2	2	3.488	88.6	170	5	200	100
7223-400150	4	102.0	2	4.527	115.0	225	6	150	100

Packaging: Coils
Couplings: Permanent crimp: refer to CrimpSource® @ www.safehose.com
 Other coupling options: refer to NAHAD Industrial Hose Assembly Guidelines