



Parker Hannifin Corporation
Industrial Hose Division
17295 Foltz Industrial Pkwy
Strongsville, OH 44149
Telephone: (440) 268-2120
Fax: (440) 268-2230
www.safehose.com

PRODUCT INFORMATION

Series SW353 and SW355 Petroleum Suction and Discharge Hose – Obsolete

Refer to Series 7330 Heavy Duty Petroleum Suction and Discharge Hose



To streamline the petroleum hose product offering, Series SW353 and SW355 suction and discharge hose will be obsolete when current inventory is depleted. The discontinuation applies to both standard and non-standard part numbers within the respective product lines, and all quotations will be expired with the discontinuation. Parker continues to offer Series 7330 heavy duty suction and discharge hose as a suggested replacement.

If there are any questions please contact
Parker Customer Service toll-free at:

866.810.HOSE (4673)
Strongsville, OH
Eastern USA

800.242.HOSE (4673)
South Gate, CA
Western USA

(Continued on page 2)



Series SW353 and SW355 Petroleum Suction & Discharge Hose – Obsolete

Refer to Series 7330 Heavy Duty Petroleum Suction & Discharge Hose

	<u>Series 7330</u>	<u>Series SW353</u>	<u>Series SW355</u>
Tube:	Black nitrile	Black nitrile	Black nitrile
Reinforcement:	Multiple textile plies w/ wire helix	Multiple textile plies w/ dual helix	Multiple textile plies w/ dual helix
Cover:	Black Neoprene; wrapped finish	Black nitrile; wrapped finish	Black nitrile; wrapped finish
Temp Range:	-40°F to +180°F	-40°F to +180°F	-40°F to +180°F
Size Range:	1-1/4" to 8"	1-1/4" to 8"	3" to 6"
Design Factor:	4:1	4:1	4:1
Brand Method:	Red text on white stripe	Black text on red stripe	Black text on red stripe
Brand Example:	PARKER SERIES 7330 HD TANK TRUCK 300 PSI MAX WP MADE IN USA 001		
Applications:	Petroleum suction and discharge; tank trucks		
Compare To:	Veyance Plicord Super Black Flexwing		

Part Number	ID (in)	ID (mm)	Reinf Layers	OD (in)	OD (mm)	Approx Wt (lbs)/100 ft	Min Bend Rad (in)	Max Rec WP (psi)	Std Pack Qty (ft)
7330-1250	1-1/4	31.8	2	1.686	42.8	71	6	300	100
7330-1500	1-1/2	38.1	2	1.976	50.2	100	8	300	100
7330-2000	2	50.8	4	2.622	66.6	166	8	300	100
7330-3000	3	76.2	4	3.654	92.8	241	15	300	100
7330-4000	4	102.0	4	4.840	122.9	387	20	300	100
7330-5000	5	127.0	4	5.882	149.4	541	25	300	100
7330-6000	6	152.4	4	7.110	180.6	665	36	300	100
7330-8000	8	203.2	6	9.118	231.6	1157	48	300	50
SW353-1250	1-1/4	31.8	2	1.750	44.6	64	5	200	100
SW353-1500	1-1/2	38.1	2	2.063	52.4	78	6	200	100
SW353-2000	2	50.8	2	2.563	65.1	107	8	200	100
SW353-2500	2-1/2	63.5	2	3.125	79.4	149	10	200	100
SW353-3000	3	76.2	2	3.563	90.5	207	12	200	100
SW353-4000	4	102.0	2	4.563	115.9	286	18	200	100
SW353-5000	5	127.0	2	5.625	142.9	370	25	150	100
SW353-6000	6	152.4	2	6.750	171.5	483	30	150	100
SW353-8000	8	203.2	4	9.250	235.0	121	42	150	100
SW355-3000	3	76.2	4	4.000	101.6	284	12	300	100
SW355-4000	4	102.0	4	5.000	127.0	384	16	300	100
SW355-6000	6	152.4	4	7.000	177.8	738	36	300	100

Packaging: Coils
Couplings: Permanent crimp: refer to CrimpSource® @ www.safehose.com
 Other coupling options: refer to NAHAD Industrial Hose Assembly Guidelines