



Parker Hannifin Corporation  
Industrial Hose Division  
17295 Foltz Industrial Pkwy  
Strongsville, OH 44149  
Telephone: (440) 268-2120  
Fax: (440) 268-2230  
www.safehose.com

## PRODUCT INFORMATION

### Series SS242, 7225 & 7351 Softwall

### Petroleum Discharge Hose – Obsolete

*Refer to Series SS107 Softwall Petroleum Discharge Hose*



To streamline the petroleum hose product offering, Series SS242, 7225 & 7351 softwall discharge hose will be obsolete effective June 1, 2010. The discontinuation applies to both standard and non-standard part numbers within the respective product lines, and all quotations will be expired with the discontinuation. Parker continues to offer Series SS107 softwall discharge hose as a suggested replacement.

If there are any questions please contact  
Parker Customer Service toll-free at:

866.810.HOSE (4673)  
Strongsville, OH  
Eastern USA

800.242.HOSE (4673)  
South Gate, CA  
Western USA

*(Continued on page 2)*

PA 2010.04.008 Series SS242, 7225, 7351 OBS - SS107 REPL



## Series SS242, 7225 & 7351 Softwall Petroleum Discharge Hose – Obsolete

*Refer to Series SS107 Softwall Petroleum Discharge Hose*

	<u>Series SS107</u>	<u>Series SS242</u>	<u>Series 7225</u>
<b>Tube:</b>	Black nitrile	Black nitrile	Black nitrile
<b>Reinforcement:</b>	Mult. textile plies w/ static wire	Mult. textile plies w/ static wire	Mult. textile plies w/ static wire
<b>Cover:</b>	Black nitrile; wrapped finish	Black nitrile; wrapped finish	Red Neoprene; wrapped finish
<b>Temp Range:</b>	-40°F to +180°F	-40°F to +180°F	-20°F to +180°F
<b>Size Range:</b>	1-1/4" to 6"	2" to 6"	1-1/2" to 4"
<b>Design Factor:</b>	4:1	4:1	4:1
<b>Brand Method:</b>	Black text on red stripe	Black text on red stripe	Black text on red stripe
<b>Brand Example:</b>	PARKER SS107 PETROLEUM DISCHARGE HOSE 2" 200 PSI WP (Caution) MADE IN USA		
<b>Applications:</b>	Petroleum discharge; tank trucks		
<b>Compare To:</b>	Gates Steer; Veyance Plicord Fuel Discharge		

Part Number	ID (in)	ID (mm)	Reinf Layers	OD (in)	OD (mm)	Approx Wt (lbs)/100 ft	Min Bend Rad (in)	Max Rec WP (psi)	Std Pack Qty (ft)
SS107-1250	1-1/4	31.8	2	1.625	41.3	46	N/A	250	100
SS107-1500	1-1/2	38.1	2	1.875	47.6	52	N/A	250	100
SS107-2000	2	50.8	2	2.375	60.3	67	N/A	200	100
SS107-3000	3	76.2	2	3.500	88.9	114	N/A	200	100
SS107-4000	4	102.0	2	4.500	114.3	146	N/A	150	100
SS107-6000	6	152.4	2	6.625	168.3	296	N/A	150	100
SS242-2000	2	50.8	2	2.688	68.3	121	N/A	200	100
SS242-3000	3	76.2	2	3.688	93.7	170	N/A	150	100
SS242-4000	4	102.0	2	4.668	119.1	226	N/A	125	100
SS242-6000	6	152.4	2	6.668	169.4	330	N/A	100	100
7225-1500	1-1/2	38.1	2	2.000	50.8	83	N/A	200	100
7225-2000	2	50.8	2	2.500	63.5	108	N/A	200	100
7225-3000	3	76.2	2	3.500	88.9	156	N/A	200	100
7225-4000	4	102.0	2	4.610	117.1	228	N/A	200	100

**Packaging:** Coils  
**Couplings:** Permanent crimp: refer to CrimpSource® @ [www.safehose.com](http://www.safehose.com)  
 Other coupling options: refer to NAHAD Industrial Hose Assembly Guidelines