



## Sales Advisory

Parker Hannifin Corporation  
Industrial Hose Division  
17295 Foltz Industrial Pkwy  
Strongsville, OH 44149  
Telephone: (440) 268-2120  
Fax: (440) 268-2230  
www.safehose.com

### PRODUCT INFORMATION

#### **Series 7224 Softwall Petroleum Discharge Hose – Obsolete**

*Refer to Series SS107R Softwall Petroleum Discharge Hose*



To streamline the petroleum hose product offering, Series 7224 softwall discharge hose will be obsolete when current inventory is depleted. The discontinuation applies to both standard and non-standard part numbers within the product line, and all quotations will be expired with the discontinuation. Parker continues to offer Series SS107R (red) softwall discharge hose as a suggested replacement.

If there are any questions please contact  
Parker Customer Service toll-free at:

866.810.HOSE (4673)  
Strongsville, OH  
Eastern USA

800.242.HOSE (4673)  
South Gate, CA  
Western USA

*(Continued on page 2)*

PA 2010.04.009 Series 7224 OBS - SS107R REPL

ENGINEERING YOUR SUCCESS.



## Series 7224 Softwall Petroleum Discharge Hose – Obsolete

*Refer to Series SS107R Softwall Petroleum Discharge Hose*

	<u>Series SS107R (Red)</u>	<u>Series 7224</u>
<b>Tube:</b>	Black nitrile	Black nitrile
<b>Reinforcement:</b>	Multiple textile plies w/ static wire	Multiple textile plies w/ static wire
<b>Cover:</b>	Red nitrile; wrapped finish	Red Neoprene; wrapped finish
<b>Temp Range:</b>	-40°F to +180°F	-20°F to +180°F
<b>Size Range:</b>	1-1/4" to 6"	1-1/2" to 4"
<b>Design Factor:</b>	4:1	4:1
<b>Brand Method:</b>	White text on red stripe	White text on red stripe
<b>Brand Example:</b>	PARKER SS107R PETROLEUM DISCHARGE HOSE 200 PSI MAX WP (Caution) MADE IN USA	
<b>Applications:</b>	Petroleum discharge; tank trucks	
<b>Compare To:</b>	Gates Steer; Veyance Plicord Fuel Discharge	

Part Number	ID (in)	ID (mm)	Reinf Layers	OD (in)	OD (mm)	Approx Wt (lbs)/ 100 ft	Min Bend Rad (in)	Max Rec WP (psi)	Std Pack Qty (ft)
SS107R-1500	1-1/2	38.1	2	1.875	47.6	52	N/A	250	100
SS107R-2000	2	50.8	2	2.375	60.3	67	N/A	200	100
SS107R-3000	3	76.2	2	3.500	88.9	114	N/A	200	100
SS107R-4000	4	102.0	2	4.500	114.3	146	N/A	150	100
7224-1500	1-1/2	38.1	2	2.000	50.8	83	N/A	200	100
7224-2000	2	50.8	2	2.500	63.5	108	N/A	200	100
7224-3000	3	76.2	2	3.500	88.9	156	N/A	200	100
7224-4000	4	102.0	2	4.610	117.1	228	N/A	200	100

**Packaging:** Coils

**Couplings:** Permanent crimp: refer to CrimpSource® @ [www.safehose.com](http://www.safehose.com)  
Other coupling options: refer to NAHAD Industrial Hose Assembly Guidelines

**WARNING:** Non-crimp couplings applied with bands or clamps may reduce the working pressure of the hose assembly to less than that of the maximum rated working pressure of the hose. Refer to the NAHAD Industrial Hose Assembly Specification Guidelines for working pressure information.