



Sales Advisory

Parker Hannifin Corporation
Industrial Hose Division
17295 Foltz Industrial Pkwy
Strongsville, OH 44149
Telephone: (440) 268-2120
Fax: (440) 268-2230
www.safehose.com

PRODUCT INFORMATION

Series SW508 Spartan™ and Series 7208 BS&W™

Oil Field Suction Hose – Obsolete

Refer to Series 7208E BS&W™ Equalizer Oil Field Suction Hose



To streamline the oil field hose product offering, Series SW508 Spartan and Series 7208 BS&W oil field suction hose will be obsolete when current inventory is depleted. The discontinuation applies to both standard and non-standard part numbers within the respective product lines, and all quotations will be expired with the discontinuation. Parker continues to offer Series 7208E BS&W Equalizer oil field suction hose as a suggested replacement.

If there are any questions please contact
Parker Customer Service toll-free at:

866.810.HOSE (4673)
Strongsville, OH
Eastern USA

800.242.HOSE (4673)
South Gate, CA
Western USA

(Continued on page 2)

PA 2010.04.010 Series SW508 & 7208 OBS - 7208E REPL

ENGINEERING YOUR SUCCESS.



**Series SW508 Spartan™ and Series 7208 BS&W™
Oil Field Suction Hose – Obsolete**

Refer to Series 7208E BS&W™ Equalizer Oil Field Suction Hose

	<u>Series 7208E</u>	<u>Series SW508</u>	<u>Series 7208</u>
Tube:	Black nitrile/SBR blend	Black nitrile blend	Black nitrile/SBR blend
Reinforcement:	Mult. textile plies w/ wire helix	Mult. text. plies w/ dual wire helix	Mult. textile plies w/ wire helix
Cover:	Black nitrile/SBR blend; wrap finish	Black nitrile blend; wrap finish	Black nitrile/SBR blend; wrap finish
Temp Range:	-22°F to +185°F	-40°F to +180°F	-22°F to +185°F
Size Range:	1-1/2" to 6"	2" to 4"	1-1/2" to 6"
Design Factor:	3:1	4:1	4:1
Brand Method:	White text on blue stripe	Black text on blue stripe	White text on blue stripe
Brand Example:	PARKER SERIES 7208E BS&W™ OIL FIELD SUCTION HOSE (NOT FOR REFINED FUELS) 150 MAX PSI WP		
Applications:	Oil field waste recovery		
Compare To:	Jason Tupelo 4677; Kuriyama T601AA; Texcel Tex-Vac; Veyance Flextra Oilfield		

Part Number	ID (in)	ID (mm)	Reinf Layers	OD (in)	OD (mm)	Approx Wt (lbs)/100 ft	Min Bend Rad (in)	Max Rec WP (psi)	Std Pack Qty (ft)
7208E-1500	1-1/2	38.1	2	1.930	49.0	86	6	150	100
7208E-2000	2	50.8	2	2.440	62.0	121	8	150	100
7208E-2500	2-1/2	63.5	2	3.010	76.5	147	10	150	100
7208E-3000	3-3/100	77.0	2	3.540	89.9	177	12	150	100
7208E-4000	4	102.0	2	4.570	116.1	258	16	150	100
7208E-6000	6	152.4	3	6.610	167.9	474	26	150	100
SW508-2000	2	50.8	2	2.500	63.5	95	10	150	100
SW508-3000	3	76.2	2	3.500	88.9	169	14	150	100
SW508-4000	4	102.0	2	4.500	114.3	247	22	150	100
7208-1000	1	25.4	2	1.410	35.8	46	2	150	100
7208-1250	1-1/4	31.8	2	1.660	42.2	55	3	150	100
7208-1500	1-1/2	38.1	2	2.010	51.1	87	4	150	100
7208-2000	2	50.8	2	2.510	63.8	112	6	150	100
7208-2500	2-1/2	63.5	2	3.010	76.5	145	9	150	100
7208-3000	3	76.2	2	3.530	89.7	186	12	150	100
7208-4000	4	102.0	2	4.590	116.6	294	16	150	100
7208-6000	6	152.4	4	6.800	172.7	556	48	150	100

Packaging: Coils
Couplings: Permanent crimp: refer to CrimpSource® @ www.safehose.com
 Other coupling options: refer to NAHAD Industrial Hose Assembly Guidelines