



Sales Advisory

Parker Hannifin Corporation
Industrial Hose Division
17295 Foltz Industrial Pkwy
Strongsville, OH 44149
Telephone: (440) 268-2120
Fax: (440) 268-2230
www.safehose.com

PRODUCT INFORMATION

Series SS145 Heavy Duty Oil and Gas Hose – Obsolete

Refer to Series ES145 Heavy Duty Oil and Gas Hose



To streamline the petroleum hose product offering, Series SS145 heavy duty oil and gas hose will be obsolete when current inventory is depleted. The discontinuation applies to both standard and non-standard part numbers within the product line, and all quotations will be expired with the discontinuation. Series ES145 is a suggested replacement for Series SS145. Specifications for Series ES145 are for reference only. Contact Parker for a quotation of this Custom Made Hose product.

If there are any questions please contact
Parker Customer Service toll-free at:

866.810.HOSE (4673)
Strongsville, OH
Eastern USA

800.242.HOSE (4673)
South Gate, CA
Western USA

(Continued on page 2)

PA 2010.04.012 Series SS145 OBS - ES145 REPL

ENGINEERING YOUR SUCCESS.



Series SS145 Heavy Duty Oil and Gas Hose – Obsolete

Refer to Series ES145 Heavy Duty Oil and Gas Hose

	<u>Series ES145</u>	<u>Series SS145</u>
Tube:	Black nitrile	Black nitrile
Reinforcement:	Multiple textile plies w/ static wire	Multiple textile plies w/ static wire
Cover:	Black nitrile; wrapped finish	Black nitrile; wrapped finish
Temp Range:	-40°F to +180°F	-40°F to +180°F
Size Range:	1-1/2" to 6"	1-1/2" to 6"
Design Factor:	4:1	4:1
Brand Method:	Black text on yellow stripe	Black text on yellow stripe
Brand Example:	PARKER SERIES ES145 HEAVY DUTY OIL AND GAS HOSE 300 PSI WP MADE IN USA	
Applications:	Petroleum suction and discharge; tank trucks	
Compare To:	Veyance Plicord Super Black Flexwing	

Part Number	ID (in)	ID (mm)	Reinf Layers	OD (in)	OD (mm)	Approx Wt (lbs)/ 100 ft	Min Bend Rad (in)	Max Rec WP (psi)	Std Pack Qty (ft)
ES145-1500	1-1/2	38.1	4	2.375	60.3	150	NA	300	100
ES145-2000	2	50.8	4	2.875	73.0	180	NA	300	100
ES145-3000	3	77.0	4	3.875	98.4	260	NA	300	100
ES145-4000	4	102.0	4	4.875	123.8	330	NA	300	100
ES145-6000	6	152.4	6	7.063	179.4	570	NA	300	100
SS145-1500	1-1/2	38.1	4	2.375	60.3	134	NA	300	100
SS145-2000	2	50.8	4	2.875	73.0	169	NA	300	100
SS145-3000	3	76.2	4	3.875	98.4	234	NA	300	100
SS145-4000	4	102.0	4	4.875	123.8	311	NA	300	100
SS145-6000	6	152.4	6	7.063	179.4	564	NA	300	100

Packaging: Coils

Couplings: Permanent crimp: refer to CrimpSource® @ www.safehose.com
Other coupling options: refer to NAHAD Industrial Hose Assembly Guidelines

WARNING: Non-crimp couplings applied with bands or clamps may reduce the working pressure of the hose assembly to less than that of the maximum rated working pressure of the hose. Refer to the NAHAD Industrial Hose Assembly Specification Guidelines for working pressure information.