



## Sales Advisory

Parker Hannifin Corporation  
Industrial Hose Division  
17295 Foltz Industrial Pkwy  
Strongsville, OH 44149  
Telephone: (440) 268-2120  
Fax: (440) 268-2230  
www.safehose.com

### PRODUCT INFORMATION

#### **Series SW501 Spartan™ Water Suction Hose – Obsolete**

*Refer to Series 7392E Super-Flex® Equalizer Water Suction and Discharge Hose*



To streamline the water hose product offering, Series SW501 Spartan water suction hose will be obsolete with production as of July 1, 2010. The discontinuation applies to both standard and non-standard part numbers within Series SW501, and all quotations will be expired with the discontinuation. Parker continues to offer Series 7392E Super-Flex Equalizer water suction and discharge hose as a possible alternative.

*Please see comparison chart on reverse.*

If there are any questions please contact  
Parker Customer Service toll-free at:

866.810.HOSE (4673)  
Strongsville, OH  
Eastern USA

800.242.HOSE (4673)  
South Gate, CA  
Western USA

*(Continued on page 2)*

PA 2010.06.013 Series SW501 OBS - 7293E REPL

ENGINEERING YOUR SUCCESS.



## Series SW501 Spartan™ Water Suction Hose – Obsolete

*Refer to Series 7392E Super-Flex® Equalizer Water Suction and Discharge Hose*

	<u>Series 7392E</u>	<u>Series SW501</u>
<b>Tube:</b>	Black EPDM	Black EPDM
<b>Reinforcement:</b>	Multiple textile plies w/ wire helix	Multiple textile plies w/ dual wire helix
<b>Cover:</b>	Black EPDM; wrapped finish	Black EPDM; wrapped finish
<b>Temp Range:</b>	-22°F to +185°F	-40°F to +200°F
<b>Size Range:</b>	1-1/2" to 6"	2" to 4"
<b>Design Factor:</b>	3:1	4:1
<b>Brand Method:</b>	White text on blue stripe	Black text on blue stripe
<b>Brand Example:</b>	PARKER SERIES 7392E WATER SUCTION & DISCHARGE HOSE 150 MAX WP	
<b>Applications:</b>	Water suction and discharge; light chemicals	
<b>Compare To:</b>	Gates Barracuda; Veyance Con-Ag Water S&D	

Part Number	ID (in)	ID (mm)	Reinf Layers	OD (in)	OD (mm)	Approx Wt (lbs)/ 100 ft	Min Bend Rad (in)	Max Rec WP (psi)	Std Pack Qty (ft)
7392E-2000	2	50.8	2	2.449	62.2	110	7	150	100
7392E-3000	3	76.2	2	3.543	90.0	198	10	150	100
7392E-4000	4	102.0	2	4.528	115.0	290	22	100	100
SW501-2000	2	50.8	2	2.438	61.9	72	10	150	100
SW501-3000	3	76.2	2	3.438	87.3	129	16	150	100
SW501-4000	4	102.0	2	4.460	113.3	195	24	150	100

**Packaging:** Coils

**Couplings:** Permanent crimp: refer to CrimpSource® @ [www.safehose.com](http://www.safehose.com)  
Other coupling options: refer to NAHAD Industrial Hose Assembly Guidelines

**WARNING:** Non-crimp couplings applied with bands or clamps may reduce the working pressure of the hose assembly to less than that of the maximum rated working pressure of the hose. Refer to the NAHAD Industrial Hose Assembly Specification Guidelines for working pressure information.