



Parker Hannifin Corporation
Industrial Hose Division
17295 Foltz Industrial Pkwy
Strongsville, OH 44149
Telephone: (440) 268-2120
Fax: (440) 268-2230
www.safehose.com

PRODUCT INFORMATION

Series SS115, SS715 Sea Lion™ and 7306M Day-Flo® Water Discharge Hose - Obsolete

Refer to Series 7306E Day-Flo® Equalizer Water Discharge Hose



To streamline the water hose product offering, Series SS115, SS715 Sea Lion and 7306M Day-Flo water discharge hose will be obsolete with production as of July 1, 2010. The discontinuation applies to both standard and non-standard part numbers within the respective series, and all quotations will be expired with the discontinuation. Parker continues to offer Series 7306E Day-Flo Equalizer water discharge hose as a possible alternative.

Please see comparison chart on reverse.

If there are any questions please contact
Parker Customer Service toll-free at:

866.810.HOSE (4673)
Strongsville, OH
Eastern USA

800.242.HOSE (4673)
South Gate, CA
Western USA

(Continued on page 2)

PA 2010.06.014 Series SS115, SS715, 7306M OBS - 7306E REPL



Series SS115, SS715 and 7306M Obsolete

Refer to Series 7306E Day-Flo® Equalizer Water Discharge Hose

	<u>Series 7306E</u>	<u>Series SS115</u>	<u>Series SS715</u>
Tube:	Black EPDM	Black SBR	Black EPDM
Reinforcement:	Multiple textile plies	Multiple textile plies	Multiple textile plies
Cover:	Black EPDM; wrapped finish	Black SBR; wrapped finish	Black EPDM; wrapped finish
Temp Range:	-22°F to +185°F	-40°F to +180°F	-40°F to +200°F
Size Range:	1-1/2" to 8"	1-1/2" to 8"	2" to 6"
Design Factor:	3:1	3:1	3:1
Brand Method:	White text on blue stripe	Unbranded	Unbranded
Brand Example:	PARKER SERIES 7306E WATER DISCHARGE HOSE 150 PSI MAX WP		
Applications:	Water discharge; light chemical discharge		
Compare To:	Vevance Versiflo 125		

Part Number	ID (in)	ID (mm)	Reinf Layers	OD (in)	OD (mm)	Approx Wt (lbs)/100 ft	Min Bend Rad (in)	Max Rec WP (psi)	Std Pack Qty (ft)
7306E-1500	1-1/2	38.1	2	1.800	45.7	42	N/A	150	100
7306E-2000	2	50.8	2	2.350	59.7	65	N/A	150	100
7306E-2500	2-1/2	63.5	2	2.880	73.2	80	N/A	150	100
7306E-3000	3	76.2	2	3.503	89.0	125	N/A	150	100
7306E-4000	4	102.0	2	4.450	113.0	140	N/A	150	100
7306E-6000	6	152.4	2	6.450	163.8	200	N/A	150	100
7306E-8000	8	203.2	2	8.500	215.9	280	N/A	100	50
SS115-1500	1-1/2	38.1	2	1.875	47.6	43	N/A	100	100
SS115-2000	2	50.8	2	2.438	61.9	54	N/A	100	100
SS115-2500	2-1/2	63.5	2	2.875	73.3	67	N/A	100	100
SS115-3000	3	76.2	2	3.438	87.3	80	N/A	100	100
SS115-4000	4	102.0	2	4.438	112.7	107	N/A	100	100
SS115-5000	5	127.0	2	5.438	138.1	133	N/A	100	100
SS115-6000	6	152.4	2	6.438	163.5	160	N/A	75	100
SS115-8000	8	203.2	4	8.563	217.5	299	N/A	75	50
SS715-2000	2	50.8	2	2.313	58.8	51	N/A	125	100
SS715-2500	2-1/2	63.5	2	2.813	71.4	68	N/A	125	100
SS715-3000	3	76.2	2	3.375	85.7	82	N/A	125	100
SS715-4000	4	102.0	2	4.375	111.1	113	N/A	125	100
SS715-6000	6	152.4	2	6.375	161.9	171	N/A	100	100
7306M-5000	5	127.0	2	5.465	138.8	213	N/A	150	100
7306M-6000	6	152.4	2	6.488	164.8	269	N/A	150	100
7306M-8000	8	203.2	4	8.543	217.0	395	N/A	150	100
7306M-10000	10	254.0	4	10.535	267.6	482	N/A	150	50
7306M-12000	12	304.8	4	12.622	320.6	617	N/A	150	50

Packaging: Coils
Couplings: Permanent crimp: refer to CrimpSource® @ www.safehose.com
 Other coupling options: refer to NAHAD Industrial Hose Assembly Guidelines