



Parker Hannifin Corporation
Industrial Hose Division
17295 Foltz Industrial Pkwy
Strongsville, OH 44149
Telephone: (440) 268-2120
Fax: (440) 268-2230
www.safehose.com

PRODUCT INFORMATION

Series SS104 Water Discharge Hose – Obsolete

Refer to Series 7306H Water Discharge Hose



To streamline the water hose product offering, Series SS104 water discharge hose will be obsolete with production as of July 1, 2010. The discontinuation applies to both standard and non-standard part numbers within Series SS104, and all quotations will be expired with the discontinuation. Parker continues to offer Series 7306H water discharge hose as a possible alternative.

Please see comparison chart on reverse side.

If there are any questions please contact
Parker Customer Service toll-free at:

866.810.HOSE (4673)
Strongsville, OH
Eastern USA

800.242.HOSE (4673)
South Gate, CA
Western USA

(Continued on page 2)

PA 2010.06.015 Series SS104 OBS - 7306H REPL



Series SS104 Water Discharge Hose – Obsolete

Refer to Series 7306H Water Discharge Hose

	<u>Series 7306H</u>	<u>Series SS104</u>
Tube:	Black EPDM	Black SBR
Reinforcement:	Multiple textile plies	Multiple textile plies
Cover:	Black EPDM; wrapped finish	Black SBR; wrapped finish
Temp Range:	-30°F to +212°F	-40°F to +180°F
Size Range:	1-1/2" to 12"	3" to 8"
Design Factor:	3:1	4:1
Brand Method:	White text on blue stripe	Unbranded
Brand Example:	PARKER SERIES 7306H DAY-FLO HD WATER DISCHARGE HOSE 200 MAX WP MADE IN USA 001	
Applications:	Water discharge	
Compare To:	Gates Dolphin; Thermoid WD 150; Veyance Plicord Water Discharge 150; Veyance Versiflo 125	

Part Number	ID (in)	ID (mm)	Reinf Layers	OD (in)	OD (mm)	Approx Wt (lbs)/100 ft	Min Bend Rad (in)	Max Rec WP (psi)	Std Pack Qty (ft)
7306H-3000	3	76.2	4	3.550	90.2	156	N/A	200	100
7306H-3500	3-1/2	88.9	4	4.056	103.0	185	N/A	200	100
7306H-4000	4	102.0	4	4.556	115.7	210	N/A	200	100
7306H-4500	4-1/2	114.3	4	5.082	129.1	250	N/A	200	100
7306H-5000	5	127.0	4	5.582	141.8	275	N/A	200	100
7306H-6000	6	152.4	4	6.646	168.8	330	N/A	200	100
7306H-8000	8	203.2	4	8.646	219.6	435	N/A	200	50
SS104-3000	3	76.2	4	3.625	92.1	136	N/A	200	100
SS104-3500	3-1/2	88.9	4	4.000	101.6	146	N/A	200	100
SS104-4000	4	102.0	4	4.625	117.5	181	N/A	200	100
SS104-4500	4-1/2	114.3	4	5.125	130.2	207	N/A	200	100
SS104-5000	5	127.0	4	5.625	142.9	229	N/A	200	100
SS104-5625	5-9/16	141.3	4	6.063	154.0	235	N/A	200	100
SS104-6000	6	152.4	4	6.625	168.3	282	N/A	200	100
SS104-6625	6-5/8	168.3	4	7.250	184.2	344	N/A	200	100
SS104-8000	8	203.2	4	8.625	219.1	384	N/A	200	100

Packaging: Coils
Couplings: Permanent crimp: refer to CrimpSource® @ www.safehose.com
 Other coupling options: refer to NAHAD Industrial Hose Assembly Guidelines

WARNING: Non-crimp couplings applied with bands or clamps may reduce the working pressure of the hose assembly to less than that of the maximum rated working pressure of the hose. Refer to the NAHAD Industrial Hose Assembly Specification Guidelines for working pressure information.