



Parker Hannifin Corporation  
Industrial Hose Division  
17295 Foltz Industrial Pkwy  
Strongsville, OH 44149  
Telephone: (440) 268-2120  
Fax: (440) 268-2230  
www.safehose.com

## PRODUCT INFORMATION

### Series 7281 Dragon Breath<sup>®</sup> Hot Air Hose – Obsolete

*Refer to Series SW360 Dragon Breath<sup>®</sup> Hot Air Blower Hose*



To streamline the air/multi-purpose and material handling hose product offering, Series 7281 Dragon Breath hot air hose will be obsolete with production as of July 1, 2010. The discontinuation applies to both standard and non-standard part numbers within Series 7281, and all quotations will be expired with the discontinuation. Parker continues to offer Series SW360 Dragon Breath hot air hose as a possible alternative.

*Please see comparison chart on reverse side.*

If there are any questions please contact  
Parker Customer Service toll-free at:

866.810.HOSE (4673)  
Strongsville, OH  
Eastern USA

800.242.HOSE (4673)  
South Gate, CA  
Western USA

*(Continued on page 2)*



## Series 7281 Dragon Breath® Hot Air Hose – Obsolete

*Refer to Series SW360 Dragon Breath® Hot Air Blower Hose*

	<u>Series SW360</u>	<u>Series 7281</u>
<b>Tube:</b>	Black EPDM	Black EPDM
<b>Reinforcement:</b>	Multiple textile plies w/ dual wire helix	Multiple textile plies with wire helix
<b>Cover:</b>	Black EPDM; wrapped finish	Black EPDM; wrapped finish
<b>Temp Range:</b>	-40°F to +350°F	-30°F to +300/350°F
<b>Size Range:</b>	2" to 6"	1-1/2" to 4"
<b>Design Factor:</b>	4:1	4:1
<b>Brand Method:</b>	Black text on yellow stripe	White text on black stripe
<b>Brand Example:</b>	SW360 DRAGON BREATH HOT AIR BLOWER HOSE 2" 200 PSI WP (Caution) MADE IN USA	
<b>Applications:</b>	Hot air transfer; bulk dry material unloading	
<b>Compare To:</b>	Eaton Boston Wildcat Hot Air; Gates Hot Air Blower; Veyance Plicord Torrid Air	

Part Number	ID (in)	ID (mm)	Reinf Layers	OD (in)	OD (mm)	Approx Wt (lbs)/100 ft	Min Bend Rad (in)	Max Rec WP (psi)	Std Pack Qty (ft)
SW360-2000	2	50.8	2	2.500	53.5	97	6	200	100
SW360-3000	3	76.2	2	3.563	90.5	175	12	200	100
SW360-4000	4	102.0	2	4.563	115.9	241	16	125	100
SW360-6000	6	152.4	2	6.813	173.1	493	24	100	100
7281-1500	1-1/2	38.1	2	2.055	52.2	87	4	175	100
7281-2000	2	50.8	2	2.565	65.1	126	6	175	100
7281-3000	3	76.2	2	3.571	90.7	200	12	175	100
7281-4000	4	102.0	2	4.614	117.2	278	16	175	100

**Packaging:** Coils  
**Couplings:** Permanent crimp: refer to CrimpSource® @ [www.safehose.com](http://www.safehose.com)  
 Other coupling options: refer to NAHAD Industrial Hose Assembly Guidelines

**WARNING:** Non-crimp couplings applied with bands or clamps may reduce the working pressure of the hose assembly to less than that of the maximum rated working pressure of the hose. Refer to the NAHAD Industrial Hose Assembly Specification Guidelines for working pressure information.

*Not recommended for use with cam and groove couplings.*