



Sales Advisory

Parker Hannifin Corporation
Industrial Hose Division
17295 Foltz Industrial Pkwy
Strongsville, OH 44149
Telephone: (440) 268-2120
Fax: (440) 268-2230
www.safehose.com

PRODUCT UPDATE

Series 7218 Driline[®] Cement Hose – Obsolete

Refer to Series SS135, SS147 and SS247



To streamline the material handling hose product offering, Series 7218 Driline cement hose will be obsolete effective with production of July 1, 2010. The discontinuation applies to both standard and non-standard part numbers within Series 7218, and all quotations will be expired with the discontinuation. Parker continues to offer Series SS135, SS147 and SS247 (which feature different tube thicknesses) material handling hose as possible alternatives.

Please see comparison chart on reverse.

If there are any questions please contact
Parker Customer Service toll-free at:

866.810.HOSE (4673)
Strongsville, OH
Eastern USA

800.242.HOSE (4673)
South Gate, CA
Western USA

(Continued on page 2)

PA 2010.06.017 Series 7218 OBS - SS135, SS147, SS247 REPL

ENGINEERING YOUR SUCCESS.



Series 7218 Driline[®] Cement Hose – Obsolete

	<u>Series SS135</u>	<u>Series SS147</u>	<u>Series SS247</u>
Tube:	1/8" Black SBR; static cond.	3/16" Black SBR; static cond.	1/4" Black SBR; static cond.
Reinforcement:	Multiple textile plies	Multiple textile plies	Multiple textile plies
Cover:	Black SBR; wrapped finish	Black SBR; wrapped finish	Black SBR; wrapped finish
Temp Range:	-40°F to +180°F	-40°F to +180°F	-40°F to +180°F
Size Range:	4" to 6"	4"	4" to 8"
Design Factor:	4:1	4:1	4:1
Brand Method:	Black text on white stripe	Black text on green stripe	Black text on blue stripe
Brand Examples:	SS135 DRY CEMENT DISCHARGE 4" 65 PSI MAX WP (Caution) MADE IN USA SS147 DRY MATERIAL DISCHARGE 60 PSI WP (Caution) MADE IN USA SS247 HEAVY DUTY DRY CEMENT HOSE 4" 75 PSI MAX WP (Caution) MADE IN USA		

Applications: Discharge of dry abrasive materials from bulk transport trucks

Part Number	ID (in)	ID (mm)	Reinf Layers	OD (in)	OD (mm)	Approx Wt (lbs)/100 ft	Tube Thickness (in)	Max Rec WP (psi)	Std Pack Qty (ft)
SS135-4000	4	102.0	2	4.500	114.3	148	1/8	65	100
SS135-4500	4-1/2	114.3	2	5.000	127.0	170	1/8	65	100
SS135-5000	5	127.0	2	5.500	139.7	190	1/8	65	100
SS135-6000	6	152.4	2	6.500	165.1	232	1/8	65	100
SS147-4000	4	102.0	2	4.625	117.5	196	3/16	60	100
SS247-4000	4	102.0	2	4.750	120.6	250	1/4	75	100
SS247-4500	4-1/2	114.3	2	5.250	133.4	279	1/4	75	100
SS247-5000	5	127.0	2	5.750	146.1	311	1/4	75	100
SS247-6000	6	152.4	2	6.750	171.5	370	1/4	70	100
7218-4018	4	102.0	2	4.480	113.8	149	1/8	60	100
7218-40316	4	102.0	2	4.622	117.4	204	3/16	60	100
7218-4025	4	102.0	2	4.740	120.4	241	1/4	60	100
7218-4518	4-1/2	114.3	2	4.964	126.1	166	1/8	60	100
7218-45316	4-1/2	114.3	2	5.106	129.7	228	3/16	60	100
7218-4525	4-1/2	114.3	2	5.224	132.7	267	1/4	60	100
7218-5018	5	127.0	2	5.464	138.8	183	1/8	60	100
7218-50316	5	127.0	2	5.606	142.4	252	3/16	60	100
7218-5025	5	127.0	2	5.724	145.4	295	1/4	60	100
7218-6018	6	152.4	2	6.560	166.6	266	1/8	60	100
7218-60316	6	152.4	2	6.630	168.4	311	3/16	60	100
7218-6025	6	152.4	2	6.748	171.4	362	1/4	60	100

Packaging: Coils
Couplings: Permanent crimp: refer to CrimpSource[®] @ www.safehose.com
 Other coupling options: refer to NAHAD Industrial Hose Assembly Guidelines

PA 2010.06.017 Series 7218 OBS - SS135, SS147, SS247 REPL