



Sales Advisory

Parker Hannifin Corporation
Industrial Hose Division
17295 Foltz Industrial Pkwy
Strongsville, OH 44149
Telephone: (440) 268-2120
Fax: (440) 268-2230
www.safehose.com

PRODUCT INFORMATION

Series SWC393 Chem-Lite™ UHMWPE Corrugated Chemical Hose – Obsolete

Refer to Series 7373T Blue Thunder® Corrugated Chemical Hose



To streamline the chemical hose product offering, Series SWC393 Chem-Lite corrugated UHMWPE chemical hose will be obsolete effective with production of September 1, 2010. The discontinuation applies to both standard and non-standard part numbers within the product line, and all quotations will be expired with the discontinuation. Parker will continue to offer Series 7373T Blue Thunder UHMWPE chemical suction hose as a suggested replacement.

Please see comparison chart on reverse side.

If there are any questions please contact
Parker Customer Service toll-free at:

866.810.HOSE (4673)
Strongsville, OH
Eastern USA

800.242.HOSE (4673)
South Gate, CA
Western USA

(Continued on page 2)

PA 2010.06.025 Series SWC393 OBS - 7373T REPL

ENGINEERING YOUR SUCCESS.



Series SWC393 Chem-Lite™ UHMWPE Corrugated Chemical Hose – Obsolete

Refer to Series 7373T Blue Thunder® Corrugated Chemical Hose

	<u>Series 7373T</u>	<u>Series SWC393</u>
Tube:	Translucent UHMW Polyethylene	Translucent UHMW Polyethylene
Reinforcement:	Multiple textile plies w/ wire helix(es)	Multiple textile plies w/ dual wire helix
Cover:	Blue corrugated EPDM; wrapped finish	Blue corrugated EPDM; wrapped finish
Temp Range:	-40°F to +250°F	-40°F to +200°F
Size Range:	3/4" to 4"	1-1/2" to 4"
Design Factor:	4:1	4:1
Brand Method:	Blue text on yellow stripe	Blue text on yellow stripe
Brand Example:	PARKER SERIES 7373T BLUE THUNDER UHMW TUBE MAX WP 200 PSI MADE IN USA (DATE CODE)	
Applications:	Chemical suction and discharge; chemical refineries; tank trucks	
Compare To:	Boston Eaton Chemical; Gates Renegade; Veyance Fabchem	

Part Number	ID (in)	ID (mm)	Reinf Layers	OD (in)	OD (mm)	Approx Wt (lbs)/100 ft	Min Bend Rad (in)	Max Rec WP (psi)	Std Pack Qty (ft)
7373T-1500	1-1/2	38.1	2	1.965	49.9	79	5	200	100
7373T-2000	2	50.8	2	2.600	66.0	127	6	200	100
7373T-3000	3	76.2	4	3.645	92.6	212	7	200	100
7373T-4000	4	102.0	4	4.675	118.7	302	8	200	100
SWC393-1500	1-1/2	38.1	2	2.063	52.4	92	6	200	100
SWC393-2000	2	50.8	2	2.594	65.9	135	8	200	100
SWC393-3000	3	76.2	2	3.594	91.3	198	12	200	100
SWC393-4000	4	102.0	2	4.688	119.1	315	20	200	100

Packaging: Coils
Couplings: Permanent crimp: refer to CrimpSource® @ www.safehose.com
 Other coupling options: refer to NAHAD Industrial Hose Assembly Guidelines

WARNING: Non-crimp couplings applied with bands or clamps may reduce the working pressure of the hose assembly to less than that of the maximum rated working pressure of the hose. Refer to the NAHAD Industrial Hose Assembly Specification Guidelines for working pressure information.