



Parker Hannifin Corporation
Industrial Hose Division
17295 Foltz Industrial Pkwy
Strongsville, OH 44149
Telephone: (440) 268-2120
Fax: (440) 268-2230
www.safehose.com

PRODUCT INFORMATION

Series SS141 Oxygen Charging Hose – Obsolete

Refer to Series 7293 Oxygen Charging Hose



To streamline the product offering, Series SS141 oxygen charging hose will be obsolete when current inventory is depleted. The discontinuation applies to both standard and non-standard part numbers within the product line, and all quotations will be expired with the discontinuation. Parker continues to offer Series 7293 oxygen charging hose as a suggested replacement.

Contact Parker for price and availability for sizes previously offered within Series SS141, but not currently offered within Series 7293.

Please see comparison chart on reverse side.

If there are any questions please contact
Parker Customer Service toll-free at:

866.810.HOSE (4673)
Strongsville, OH
Eastern USA

800.242.HOSE (4673)
South Gate, CA
Western USA

(Continued on page 2)



Series SS141 Oxygen Charging Hose – Obsolete

Refer to Series 7293 Oxygen Charging Hose

	<u>Series 7293</u>	<u>Series SS141</u>
Tube:	Black neoprene	Black neoprene
Reinforcement:	Multiple textile plies	Multiple textile plies
Cover:	Green neoprene; wrapped finish	Green neoprene; wrapped finish
Temp Range:	-22°F to +176°F (-30°C to +80°C)	-40°F to +200°F (-40°C to +93°C)
Size Range:	1/2" to 2"	1" to 4"
Design Factor:	4:1	4:1
Brand Method:	Embossed	Embossed
Brand Example:	PARKER SERIES 7293 OXYGEN CHARGING 500 PSI MAX WP MADE IN USA (DATE CODE)	
Applications:	<ul style="list-style-type: none"> • Oxygen charging, lancing, scarfing • Foundries, steel mills 	

Part Number	ID (in)	ID (mm)	Reinf Layers	OD (in)	OD (mm)	Approx Wt (lbs/100 ft)	Max Rec WP (psi)	Std Pack Qty (ft)
7293-0500	1/2	12.7	2	0.992	25.2	38	500	100
7293-0750	3/4	19.1	2	1.276	32.4	54	500	100
7293-1000	1	25.4	2	1.528	38.3	68	500	100
7293-1250	1-1/4	31.8	2	1.930	49.0	108	500	100
7293-1500	1-1/2	38.1	2	2.174	55.2	124	500	100
7293-2000	2	50.8	4	2.764	70.2	180	500	100
SS141-1000	1	25.4	2	1.688	42.9	84	500	100
SS141-1250	1-1/4	31.8	2	1.938	49.2	101	500	100
SS141-1500	1-1/2	38.1	4	2.188	55.6	113	500	100
SS141-2000	2	50.8	4	2.750	69.9	156	500	100
SS141-3000	3	76.2	6	4.000	101.6	310	500	100
SS141-4000	4	101.6	6	5.000	127.0	400	500	100

Packaging: Coils

Couplings: Permanent crimp: refer to CrimpSource® @ www.safehose.com
Other coupling options: refer to NAHAD Industrial Hose Assembly Guidelines

WARNING: Non-crimp couplings applied with bands or clamps may reduce the working pressure of the hose assembly to less than that of the maximum rated working pressure of the hose. Refer to the NAHAD Industrial Hose Assembly Specification Guidelines for working pressure information.